

## liste des produits standard de tissus métalliques

maille	fil Ø mm	Mesh	passage %	poids kg/m <sup>2</sup>	matériau		
					galvanisé	Acier inox 1.4301	Acier inox 1.4404
0.055	0.03	300	42	0.14		X	X
0.043	0.035	325	30	0.2		X	X
0.104	0.065	150	38	0.32		X	X
0.125	0.09	120	34	0.48		X	X
0.14	0.067	120	46	0.27		X	X
0.15	0.063	120	50	0.24			X
0.2	0.125	80	39	0.63		X	X
0.265	0.1	72	53	0.6		X	X
0.31	0.11	60	55	0.36		X	X
0.45	0.22	38	45	0.92		X	X
0.5	0.16	40	57	0.51			X
0.5	0.25	34	45	1		X	X
0.6	0.16	34	62	0.44		X	X
0.8	0.2	26	64	0.52	X	X	X
0.95	0.36	20	51	1.26			X
1	0.35	19	55	1.15	X		
1.09	0.36	18	57	1.14			X
1.34	0.4	15	60	1.17			X
1.4	0.25	16	72	0.48	X		
1.4	0.22	16	74	0.4		X	X
1.5	0.5	13	56	1.63		X	X
1.6	0.28	13.5	72	0.53		X	X
1.8	0.5	11	61	1.38		X	X
1.94	0.6	10	58	1.98	X	X	X
2	0.55	10	62	1.52	X	X	X
2.28	0.63	9	62	1.73			X
2.94	0.8	7	62	2.17			X
3.15	0.8	6.5	64	2.08	X	X	X
3.46	0.9	7	62	2.36			X
4	1	5	64	2.5		X	X
4.5	1.25	4.5	61	3.52	X	X	X
5	1.25	4	64	3.13		X	X
7.1	1.4	3	70	2.94		X	X
10	1.5	2.21	79	2.82		X	X

Qualité disponible avec des panneaux standard de notre stock d'usine

Remarque : d'autres dimensions de mailles, diamètres de fils et matériaux sont disponibles sur demande.